

GT TESTER

Pocket CCTV Tester

FUNCTIONS

Video Tester

2.5" LCD monitor

Adjustable brightness, contrast and chroma

PTZ Controller

PTZ Controller (compatible with Pelco-D, Pelco-P, Vicon, VCL, Samsung, Panasonic, Kalatel, Dynacolor etc)

PTZ protocols selectable via OSD menu, compatible with most PTZ cameras

Pelco-Coaxitron makes testing easier as you only need to

connect the video cable to transmit both video and data signal

Baud Rate: 2400bps, 4800bps, 9600bps, 19200bps - selectable via OSD menu

Camera address selectable from 1-255

Can display the PTZ camera OSD menu and set all the PTZ functions

Full PTZ control



PTZ Command Analyser

Receives PTZ code so that user can analyze the PTZ command

Network Cable Tester

RJ45 testing terminal (equipped in the package) can test the network cable status, LED display and wrong information display on the screen for 8 pins connection

RS485 Polarity Tester

Can test the RS485 data cable polarity, displays on the LCD screen with + or -



FEATURES



2.5" LCD monitor. With brightness, contrast, chroma adjustable.



PAL/NTSC auto adaptable



Pocket size, easy and convenient operation



With a LCD cover, can protect the LCD monitor from scratches when putting into the tool box



2 piece 18490 Li Battery-powered or DC12V/2A power input selectable



With audio input and built-in speaker



With sleep function, can set the unit switch off automatically after a period of time without operation, ideal for save electricity.



With Macro buttons for user to set the macro function according to his specific request on F1 ,F2, F3 keys.



OSD menu On/off selectable to avoid overlap with the camera titles



With mounting stand and standard camera mounting screws, easy for hands free operation when putting it into a camera stand.

PACKAGE INCLUDES

- 1 x CCTV tester
- 1 x UTP test terminal
- 2 x Rechargeable Batteries
- 1 x DC 12V/2A power supply
- 1 x 1m video cable
- 1 x Necklace
- 1 x User Manual

OPERATING SPECIFICATIONS

<i>Work Temperature</i>	-30°C - +70°C
<i>Work Humidity</i>	30% - 90%
<i>Dimension (mm)</i>	170 x 90 x 45
<i>Inner box (cm)</i>	22.5 x 21.5 x 8.5
<i>Package</i>	10pcs/carton, 44cm x 26.5cm x 42cm, 7.8kg